

# Create Awesome LaTeX Table with knitr::kable and kableExtra

*Hao Zhu*

*2018-08-23*

## Contents

|   |           |
|---|-----------|
| <b>Overview</b>                               | <b>2</b>  |
| <b>Installation</b>                           | <b>2</b>  |
| <b>Getting Started</b>                        | <b>2</b>  |
| LaTeX packages used in this package . . . . . | 3         |
| Plain LaTeX . . . . .                         | 3         |
| LaTeX table with booktabs . . . . .           | 4         |
| <b>Table Styles</b>                           | <b>4</b>  |
| LaTeX options . . . . .                       | 4         |
| Full width? . . . . .                         | 7         |
| Position . . . . .                            | 8         |
| Font Size . . . . .                           | 9         |
| <b>Column / Row Specification</b>             | <b>9</b>  |
| Column spec . . . . .                         | 9         |
| Row spec . . . . .                            | 10        |
| Header Rows . . . . .                         | 10        |
| <b>Cell/Text Specification</b>                | <b>10</b> |
| Conditional logic . . . . .                   | 11        |
| Visualize data with Viridis Color . . . . .   | 11        |
| Text Specification . . . . .                  | 12        |
| <b>Grouped Columns / Rows</b>                 | <b>12</b> |
| Add header rows to group columns . . . . .    | 12        |
| Group rows via labeling . . . . .             | 13        |
| Row indentation . . . . .                     | 15        |
| Group rows via multi-row cell . . . . .       | 15        |
| <b>Table Footnote</b>                         | <b>18</b> |
| <b>LaTeX Only Features</b>                    | <b>20</b> |
| Linebreak processor . . . . .                 | 20        |
| Table on a Landscape Page . . . . .           | 21        |
| Use LaTeX table in HTML or Word . . . . .     | 23        |
| <b>From other packages</b>                    | <b>23</b> |
| tables . . . . .                              | 23        |

Please see the package documentation site for how to use this package in HTML and more.

## Overview

The goal of `kableExtra` is to help you build common complex tables and manipulate table styles. It imports the pipe `%>%` symbol from `magrittr` and verbalizes all the functions, so basically you can add “layers” to a kable output in a way that is similar with `ggplot2` and `plotly`.

To learn how to generate complex tables in HTML, please visit [http://haozhu233.github.io/kableExtra/awesome\\_table\\_in\\_html.html](http://haozhu233.github.io/kableExtra/awesome_table_in_html.html).



## Installation

```
install.packages("kableExtra")

# For dev version
# install.packages("devtools")
devtools::install_github("haozhu233/kableExtra")
```

## Getting Started

Here we are using the first few columns and rows from dataset `mtcars`

```
library(knitr)
library(kableExtra)
dt <- mtcars[1:5, 1:6]
```

When you are using `kable()`, if you don't specify `format`, by default it will generate a markdown table and let pandoc handle the conversion from markdown to HTML/PDF. This is the most favorable approach to render most simple tables as it is format independent. If you switch from HTML to pdf, you basically don't need to change anything in your code. However, markdown doesn't support complex table. For example, if you want to have a double-row header table, markdown just cannot provide you the functionality you need. As a result, when you have such a need, you should **define format in `kable()`** as either “html” or “latex”. *You can also define a global option at the beginning using `options(knitr.table.format = "latex")` so you don't repeat the step every time.* **In this tutorial, I'll still put `format="latex"` in the function in case users just want to quickly replicate the results. In practice, you don't need to define those formats.**

**Starting from `kableExtra` 0.9.0**, when you load this package (`library(kableExtra)`), **it will automatically set up the global option '`knitr.table.format`' based on your current environment**. Unless you are rendering a PDF, `kableExtra` will try to render a HTML table for you. **You no longer need to manually set either the global option or the format option in each `kable()` function.** I'm still including the explanation above here in this vignette so you can understand what is going on behind the scene. Note that this is only an global option. You can manually set any format in `kable()` whenever you want. I just hope you can enjoy a peace of mind in most of your time.

You can disable this behavior by setting `options(kableExtra.auto_format = FALSE)` before you load `kableExtra`.

```
# If you are using kableExtra < 0.9.0, you are recommended to set a global option first.
# options(knitr.table.format = "latex")
## If you don't define format here, you'll need put `format = "latex"`
## in every kable function.
```

## LaTeX packages used in this package

If you are using a recent version of rmarkdown, you are recommended to load this package entirely via `library(kableExtra)` or `require(kableExtra)` because this package will load all necessary LaTeX packages, such as `booktabs` or `multirow`, for you automatically. Note that, if you are calling functions from `kableExtra` via `kableExtra::kable_styling()` or if you put `library(kableExtra)` in a separate R file that is **sourced** by the rmarkdown document, these packages won't be loaded. Furthermore, you can suppress this auto-loading behavior by setting a global option `kableExtra.latex.load_packages` to be `FALSE` before you load `kableExtra`.

```
# Not evaluated. Illustration purpose
options(kableExtra.latex.load_packages = FALSE)
library(kableExtra)
```

If you are using R Sweave, beamer, R package vignette template, `tufte` or some customized rmarkdown templates, you can put the following meta data into the `yaml` section. If you are familiar with LaTeX and you know what you are doing, feel free to remove unnecessary packages from the list.

header-includes:

```
- \usepackage{booktabs}
- \usepackage{longtable}
- \usepackage{array}
- \usepackage{multirow}
- \usepackage[table]{xcolor}
- \usepackage{wrapfig}
- \usepackage{float}
- \usepackage{colortbl}
- \usepackage{pdflscape}
- \usepackage{tabu}
- \usepackage{threeparttable}
- \usepackage{threeparttablex}
- \usepackage[normalem]{ulem}
- \usepackage{makecell}
```

## Plain LaTeX

Plain LaTeX table looks relatively ugly in 2017.

```
# Again, with kableExtra >= 0.9.0, `format = "latex"` is automatically defined
# when this package gets loaded. Otherwise, you still need to define formats
kable(dt)
```

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

```
# Same: kable(dt, "latex")
```

## LaTeX table with booktabs

Similar to Bootstrap in HTML, in LaTeX, you can also use a trick to make your table look prettier as well. The different part is that, this time you don't need to pipe kable outputs to another function. Instead, you should call `booktabs = T` directly in `kable()`.

```
kable(dt, "latex", booktabs = T)
```

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

## Table Styles

`kable_styling` in LaTeX uses the same syntax and structure as `kable_styling` in HTML. However, instead of `bootstrap_options`, you should specify `latex_options` instead.

## LaTeX options

Similar with `bootstrap_options`, `latex_options` is also a character vector with a bunch of options including `striped`, `hold_position` and `scale_down`.

### Striped

Even though in the LaTeX world, people usually call it `alternative row colors` but here I'm using its bootstrap name for consistency. Note that to make it happen, LaTeX package `xcolor` is required to be loaded. In an environment like `rmarkdown::pdf_document` (rmarkdown 1.4.0 +), `kable_styling` will load it automatically if `striped` is enabled. However, in other cases, you probably need to import that package by yourself.

```
kable(dt, "latex", booktabs = T) %>%  
  kable_styling(latex_options = "striped")
```

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

### Hold position

If you provide a table caption in `kable()`, it will put your LaTeX tabular in a `table` environment, unless you are using `longtable`. A `table` environment will automatically find the best place (it thinks) to put your

table. However, in many cases, you do want your table to appear in a position you want it to be. In this case, you can use this `hold_position` options here.

```
kable(dt, "latex", caption = "Demo table", booktabs = T) %>%
  kable_styling(latex_options = c("striped", "hold_position"))
```

Table 1: Demo table

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

If you find `hold_position` is not powerful enough to literally PIN your table in the exact position, you may want to use `HOLD_position`, which is a more powerful version of this feature. For those who are familiar with LaTeX, `hold_position` uses `[!h]` and `HOLD_position` uses `[H]` and the `float` package.

## Scale down

When you have a wide table that will normally go out of the page, and you want to scale down the table to fit the page, you can use the `scale_down` option here. Note that, if your table is too small, it will also scale up your table. It was named in this way only because scaling up isn't very useful in most cases.

```
kable(cbind(dt, dt, dt), "latex", booktabs = T) %>%
  kable_styling(latex_options = c("striped", "scale_down"))
```

|                   | mpg  | cyl | disp | hp  | drat | wt    | mpg  | cyl | disp | hp  | drat | wt    | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|------|-----|------|-----|------|-------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

```
kable(cbind(dt), "latex", booktabs = T) %>%
  kable_styling(latex_options = c("striped", "scale_down"))
```

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

## Repeat header in longtable

In `kableExtra` 0.3.0 or above, a new option `repeat_header` was introduced into `kable_styling`. It will add header rows to longtables spanning multiple pages. For table captions on following pages, it will append “*continued*” to the caption to differentiate. If you need texts other than “(*continued*)” (for example, other languages), you can specify it using `kable_styling(..., repeat_header_text = "xxx")`. If you want to completely replace the table caption instead of appending, you can specify it in the option `repeat_header_method`.

```
long_dt <- rbind(mtcars, mtcars)

kable(long_dt, "latex", longtable = T, booktabs = T, caption = "Longtable") %>%
  add_header_above(c(" ", "Group 1" = 5, "Group 2" = 6)) %>%
  kable_styling(latex_options = c("repeat_header"))
```

Table 2: Longtable

|                     | Group 1 |     |       |     |      | Group 2 |       |    |    |      |      |
|---------------------|---------|-----|-------|-----|------|---------|-------|----|----|------|------|
|                     | mpg     | cyl | disp  | hp  | drat | wt      | qsec  | vs | am | gear | carb |
| Mazda RX4           | 21.0    | 6   | 160.0 | 110 | 3.90 | 2.620   | 16.46 | 0  | 1  | 4    | 4    |
| Mazda RX4 Wag       | 21.0    | 6   | 160.0 | 110 | 3.90 | 2.875   | 17.02 | 0  | 1  | 4    | 4    |
| Datsun 710          | 22.8    | 4   | 108.0 | 93  | 3.85 | 2.320   | 18.61 | 1  | 1  | 4    | 1    |
| Hornet 4 Drive      | 21.4    | 6   | 258.0 | 110 | 3.08 | 3.215   | 19.44 | 1  | 0  | 3    | 1    |
| Hornet Sportabout   | 18.7    | 8   | 360.0 | 175 | 3.15 | 3.440   | 17.02 | 0  | 0  | 3    | 2    |
| Valiant             | 18.1    | 6   | 225.0 | 105 | 2.76 | 3.460   | 20.22 | 1  | 0  | 3    | 1    |
| Duster 360          | 14.3    | 8   | 360.0 | 245 | 3.21 | 3.570   | 15.84 | 0  | 0  | 3    | 4    |
| Merc 240D           | 24.4    | 4   | 146.7 | 62  | 3.69 | 3.190   | 20.00 | 1  | 0  | 4    | 2    |
| Merc 230            | 22.8    | 4   | 140.8 | 95  | 3.92 | 3.150   | 22.90 | 1  | 0  | 4    | 2    |
| Merc 280            | 19.2    | 6   | 167.6 | 123 | 3.92 | 3.440   | 18.30 | 1  | 0  | 4    | 4    |
| Merc 280C           | 17.8    | 6   | 167.6 | 123 | 3.92 | 3.440   | 18.90 | 1  | 0  | 4    | 4    |
| Merc 450SE          | 16.4    | 8   | 275.8 | 180 | 3.07 | 4.070   | 17.40 | 0  | 0  | 3    | 3    |
| Merc 450SL          | 17.3    | 8   | 275.8 | 180 | 3.07 | 3.730   | 17.60 | 0  | 0  | 3    | 3    |
| Merc 450SLC         | 15.2    | 8   | 275.8 | 180 | 3.07 | 3.780   | 18.00 | 0  | 0  | 3    | 3    |
| Cadillac Fleetwood  | 10.4    | 8   | 472.0 | 205 | 2.93 | 5.250   | 17.98 | 0  | 0  | 3    | 4    |
| Lincoln Continental | 10.4    | 8   | 460.0 | 215 | 3.00 | 5.424   | 17.82 | 0  | 0  | 3    | 4    |
| Chrysler Imperial   | 14.7    | 8   | 440.0 | 230 | 3.23 | 5.345   | 17.42 | 0  | 0  | 3    | 4    |
| Fiat 128            | 32.4    | 4   | 78.7  | 66  | 4.08 | 2.200   | 19.47 | 1  | 1  | 4    | 1    |
| Honda Civic         | 30.4    | 4   | 75.7  | 52  | 4.93 | 1.615   | 18.52 | 1  | 1  | 4    | 2    |
| Toyota Corolla      | 33.9    | 4   | 71.1  | 65  | 4.22 | 1.835   | 19.90 | 1  | 1  | 4    | 1    |
| Toyota Corona       | 21.5    | 4   | 120.1 | 97  | 3.70 | 2.465   | 20.01 | 1  | 0  | 3    | 1    |
| Dodge Challenger    | 15.5    | 8   | 318.0 | 150 | 2.76 | 3.520   | 16.87 | 0  | 0  | 3    | 2    |
| AMC Javelin         | 15.2    | 8   | 304.0 | 150 | 3.15 | 3.435   | 17.30 | 0  | 0  | 3    | 2    |
| Camaro Z28          | 13.3    | 8   | 350.0 | 245 | 3.73 | 3.840   | 15.41 | 0  | 0  | 3    | 4    |
| Pontiac Firebird    | 19.2    | 8   | 400.0 | 175 | 3.08 | 3.845   | 17.05 | 0  | 0  | 3    | 2    |
| Fiat X1-9           | 27.3    | 4   | 79.0  | 66  | 4.08 | 1.935   | 18.90 | 1  | 1  | 4    | 1    |
| Porsche 914-2       | 26.0    | 4   | 120.3 | 91  | 4.43 | 2.140   | 16.70 | 0  | 1  | 5    | 2    |
| Lotus Europa        | 30.4    | 4   | 95.1  | 113 | 3.77 | 1.513   | 16.90 | 1  | 1  | 5    | 2    |
| Ford Pantera L      | 15.8    | 8   | 351.0 | 264 | 4.22 | 3.170   | 14.50 | 0  | 1  | 5    | 4    |
| Ferrari Dino        | 19.7    | 6   | 145.0 | 175 | 3.62 | 2.770   | 15.50 | 0  | 1  | 5    | 6    |
| Maserati Bora       | 15.0    | 8   | 301.0 | 335 | 3.54 | 3.570   | 14.60 | 0  | 1  | 5    | 8    |
| Volvo 142E          | 21.4    | 4   | 121.0 | 109 | 4.11 | 2.780   | 18.60 | 1  | 1  | 4    | 2    |

Table 2: Longtable (*continued*)

|                      | Group 1 |     |       |     |      | Group 2 |       |    |    |      |      |
|----------------------|---------|-----|-------|-----|------|---------|-------|----|----|------|------|
|                      | mpg     | cyl | disp  | hp  | drat | wt      | qsec  | vs | am | gear | carb |
| Mazda RX41           | 21.0    | 6   | 160.0 | 110 | 3.90 | 2.620   | 16.46 | 0  | 1  | 4    | 4    |
| Mazda RX4 Wag1       | 21.0    | 6   | 160.0 | 110 | 3.90 | 2.875   | 17.02 | 0  | 1  | 4    | 4    |
| Datsun 7101          | 22.8    | 4   | 108.0 | 93  | 3.85 | 2.320   | 18.61 | 1  | 1  | 4    | 1    |
| Hornet 4 Drive1      | 21.4    | 6   | 258.0 | 110 | 3.08 | 3.215   | 19.44 | 1  | 0  | 3    | 1    |
| Hornet Sportabout1   | 18.7    | 8   | 360.0 | 175 | 3.15 | 3.440   | 17.02 | 0  | 0  | 3    | 2    |
| Valiant1             | 18.1    | 6   | 225.0 | 105 | 2.76 | 3.460   | 20.22 | 1  | 0  | 3    | 1    |
| Duster 3601          | 14.3    | 8   | 360.0 | 245 | 3.21 | 3.570   | 15.84 | 0  | 0  | 3    | 4    |
| Merc 240D1           | 24.4    | 4   | 146.7 | 62  | 3.69 | 3.190   | 20.00 | 1  | 0  | 4    | 2    |
| Merc 2301            | 22.8    | 4   | 140.8 | 95  | 3.92 | 3.150   | 22.90 | 1  | 0  | 4    | 2    |
| Merc 2801            | 19.2    | 6   | 167.6 | 123 | 3.92 | 3.440   | 18.30 | 1  | 0  | 4    | 4    |
| Merc 280C1           | 17.8    | 6   | 167.6 | 123 | 3.92 | 3.440   | 18.90 | 1  | 0  | 4    | 4    |
| Merc 450SE1          | 16.4    | 8   | 275.8 | 180 | 3.07 | 4.070   | 17.40 | 0  | 0  | 3    | 3    |
| Merc 450SL1          | 17.3    | 8   | 275.8 | 180 | 3.07 | 3.730   | 17.60 | 0  | 0  | 3    | 3    |
| Merc 450SLC1         | 15.2    | 8   | 275.8 | 180 | 3.07 | 3.780   | 18.00 | 0  | 0  | 3    | 3    |
| Cadillac Fleetwood1  | 10.4    | 8   | 472.0 | 205 | 2.93 | 5.250   | 17.98 | 0  | 0  | 3    | 4    |
| Lincoln Continental1 | 10.4    | 8   | 460.0 | 215 | 3.00 | 5.424   | 17.82 | 0  | 0  | 3    | 4    |
| Chrysler Imperial1   | 14.7    | 8   | 440.0 | 230 | 3.23 | 5.345   | 17.42 | 0  | 0  | 3    | 4    |
| Fiat 1281            | 32.4    | 4   | 78.7  | 66  | 4.08 | 2.200   | 19.47 | 1  | 1  | 4    | 1    |
| Honda Civic1         | 30.4    | 4   | 75.7  | 52  | 4.93 | 1.615   | 18.52 | 1  | 1  | 4    | 2    |
| Toyota Corolla1      | 33.9    | 4   | 71.1  | 65  | 4.22 | 1.835   | 19.90 | 1  | 1  | 4    | 1    |
| Toyota Corona1       | 21.5    | 4   | 120.1 | 97  | 3.70 | 2.465   | 20.01 | 1  | 0  | 3    | 1    |
| Dodge Challenger1    | 15.5    | 8   | 318.0 | 150 | 2.76 | 3.520   | 16.87 | 0  | 0  | 3    | 2    |
| AMC Javelin1         | 15.2    | 8   | 304.0 | 150 | 3.15 | 3.435   | 17.30 | 0  | 0  | 3    | 2    |
| Camaro Z281          | 13.3    | 8   | 350.0 | 245 | 3.73 | 3.840   | 15.41 | 0  | 0  | 3    | 4    |
| Pontiac Firebird1    | 19.2    | 8   | 400.0 | 175 | 3.08 | 3.845   | 17.05 | 0  | 0  | 3    | 2    |
| Fiat X1-91           | 27.3    | 4   | 79.0  | 66  | 4.08 | 1.935   | 18.90 | 1  | 1  | 4    | 1    |
| Porsche 914-21       | 26.0    | 4   | 120.3 | 91  | 4.43 | 2.140   | 16.70 | 0  | 1  | 5    | 2    |
| Lotus Europa1        | 30.4    | 4   | 95.1  | 113 | 3.77 | 1.513   | 16.90 | 1  | 1  | 5    | 2    |
| Ford Pantera L1      | 15.8    | 8   | 351.0 | 264 | 4.22 | 3.170   | 14.50 | 0  | 1  | 5    | 4    |
| Ferrari Dino1        | 19.7    | 6   | 145.0 | 175 | 3.62 | 2.770   | 15.50 | 0  | 1  | 5    | 6    |
| Maserati Bora1       | 15.0    | 8   | 301.0 | 335 | 3.54 | 3.570   | 14.60 | 0  | 1  | 5    | 8    |
| Volvo 142E1          | 21.4    | 4   | 121.0 | 109 | 4.11 | 2.780   | 18.60 | 1  | 1  | 4    | 2    |

## Full width?

If you have a small table and you want it to spread wide on the page, you can try the `full_width` option. Unlike `scale_down`, it won't change your font size. You can use `column_spec`, which will be explained later, together with `full_width` to achieve the best result.

```
kable(dt, "latex", booktabs = T) %>%
  kable_styling(full_width = T) %>%
  column_spec(1, width = "8cm")
```

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

## Position

Table Position only matters when the table doesn't have `full_width`. You can choose to align the table to `center` or `left` side of the page. The default value of position is `center`.

Note that even though you can select to `right` align your table but the table will actually be centered. Somehow it is very difficult to right align a table in LaTeX (since it's not very useful in the real world?). If you know how to do it, please send out an issue or PR and let me know.

```
kable(dt, "latex", booktabs = T) %>%
  kable_styling(position = "center")
```

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

Besides these three common options, you can also wrap text around the table using the `float-left` or `float-right` options. Note that, like `striped`, this feature will load another non-default LaTeX package `wrapfig` which requires rmarkdown 1.4.0 +. If you rmarkdown version < 1.4.0, you need to load the package through a customized LaTeX template file.

```
kable(dt, "latex", booktabs = T) %>%
  kable_styling(position = "float_right")
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Cras sit amet mauris in ex ultricies elementum vel rutrum dolor. Phasellus tempor convallis dui, in hendrerit mauris placerat scelerisque. Maecenas accumsan enim, a maximus velit. Pellentesque in risus eget est faucibus convallis nec at nulla. Phasellus nec lacinia justo. Morbi fermentum, orci id varius accumsan, nibh neque porttitor ipsum, consectetur luctus risus arcu ac ex. Aenean a luctus augue. Suspendisse et auctor nisl. Suspendisse cursus ultrices quam non vulputate. Phasellus et pharetra neque, vel feugiat erat. Sed feugiat elit at mauris commodo consequat. Sed congue lectus id mattis hendrerit. Mauris turpis nisl, congue eget velit sed, imperdiet convallis magna. Nam accumsan urna risus, non feugiat odio vehicula eget.

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |



## Font Size

If one of your tables is huge and you want to use a smaller font size for that specific table, you can use the `font_size` option.

```
kable(dt, "latex", booktabs = T) %>%
  kable_styling(font_size = 7)
```

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

## Column / Row Specification

### Column spec

When you have a table with lots of explanatory texts, you may want to specify the column width for different column, since the auto adjust in HTML may not work in its best way while basic LaTeX table is really bad at handling text wrapping. Also, sometimes, you may want to highlight a column (e.g., a “Total” column) by making it bold. In these scenarios, you can use `column_spec()`. You can find an example below.

```
text_tbl <- data.frame(
  Items = c("Item 1", "Item 2", "Item 3"),
  Features = c(
    "Lorem ipsum dolor sit amet, consectetur adipiscing elit. Proin vehicula tempor ex. Morbi malesuada
    "In eu urna at magna luctus rhoncus quis in nisl. Fusce in velit varius, posuere risus et, cursus a
    "Vivamus venenatis egestas eros ut tempus. Vivamus id est nisi. Aliquam molestie erat et sollicitud
  )
)

kable(text_tbl, "latex", booktabs = T) %>%
  kable_styling(full_width = F) %>%
  column_spec(1, bold = T, color = "red") %>%
  column_spec(2, width = "30em")
```

| Items  | Features   |
|--------|--|
| Item 1 | Lorem ipsum dolor sit amet, consectetur adipiscing elit. Proin vehicula tempor ex. Morbi malesuada sagittis turpis, at venenatis nisl luctus a.                |
| Item 2 | In eu urna at magna luctus rhoncus quis in nisl. Fusce in velit varius, posuere risus et, cursus augue. Duis eleifend aliquam ante, a aliquet ex tincidunt in. |
| Item 3 | Vivamus venenatis egestas eros ut tempus. Vivamus id est nisi. Aliquam molestie erat et sollicitudin venenatis. In ac lacus at velit scelerisque mattis.       |

## Row spec

Similar with `column_spec`, you can define specifications for rows. Currently, you can either bold or italicize an entire row. Note that, similar to other row-related functions in `kableExtra`, for the position of the target row, you don't need to count in header rows or the group labeling rows.

```
kable(dt, "latex", booktabs = T) %>%
  kable_styling("striped", full_width = F) %>%
  column_spec(7, border_left = T, bold = T) %>%
  row_spec(1, strikeout = T) %>%
  row_spec(3:5, bold = T, color = "white", background = "black")
```

|                   | mpg  | cyl | disp | hp  | drat | wt               |
|-------------------|------|-----|------|-----|------|------------------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | <del>2.620</del> |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | <del>2.875</del> |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320            |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215            |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440            |

## Header Rows

One special case of `row_spec` is that you can specify the format of the header row via `row_spec(row = 0, ...)`.

```
kable(dt, "latex", booktabs = T, align = "c") %>%
  kable_styling(latex_options = "striped", full_width = F) %>%
  row_spec(0, angle = 45)
```

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

## Cell/Text Specification

Function `cell_spec` is introduced in version 0.6.0 of `kableExtra`. Unlike `column_spec` and `row_spec`, **this function is designed to be used before the data.frame gets into the `kable` function**. Comparing with figuring out a list of 2 dimensional indexes for targeted cells, this design is way easier to learn and use, and it fits perfectly well with `dplyr`'s `mutate` and `summarize` functions. With this design, there are two things to be noted: \* Since `cell_spec` generates raw HTML or LaTeX code, make sure you remember to put `escape = FALSE` in `kable`. At the same time, you have to escape special symbols including % manually by yourself \* `cell_spec` needs a way to know whether you want html or latex. You can specify it locally in function or globally via the `options(knitr.table.format = "latex")` method as suggested at the beginning. If you don't provide anything, this function will output as HTML by default.

Currently, `cell_spec` supports features including bold, italic, monospace, text color, background color, align, font size & rotation angle. More features may be added in the future. Please see function documentations as reference.

## Conditional logic

It is very easy to use `cell_spec` with conditional logic. Here is an example.

```
library(dplyr)
mtcars[1:10, 1:2] %>%
  mutate(
    car = row.names(.),
    # You don't need format = "latex" if you have ever defined options(knitr.table.format)
    mpg = cell_spec(mpg, "latex", color = ifelse(mpg > 20, "red", "blue")),
    cyl = cell_spec(cyl, "latex", color = "white", align = "c", angle = 45,
                    background = factor(cyl, c(4, 6, 8),
                                       c("#666666", "#999999", "#BBBBBB")))
  ) %>%
  select(car, mpg, cyl) %>%
  kable("latex", escape = F, booktabs = T, linesep = "")
```

| car               | mpg  | cyl |
|-------------------|------|-----|
| Mazda RX4         | 21   | 6   |
| Mazda RX4 Wag     | 21   | 6   |
| Datsun 710        | 22.8 | 4   |
| Hornet 4 Drive    | 21.4 | 6   |
| Hornet Sportabout | 18.7 | 8   |
| Valiant           | 18.1 | 6   |
| Duster 360        | 14.3 | 8   |
| Merc 240D         | 24.4 | 4   |
| Merc 230          | 22.8 | 4   |
| Merc 280          | 19.2 | 6   |

## Visualize data with Viridis Color

This package also comes with a few helper functions, including `spec_color`, `spec_font_size` & `spec_angle`. These functions can rescale continuous variables to certain scales. For example, function `spec_color` would map a continuous variable to any viridis color palettes. It offers a very visually impactful representation in a tabular format.

```
iris[1:10, ] %>%
  mutate_if(is.numeric, function(x) {
    cell_spec(x, "latex", bold = T, color = spec_color(x, end = 0.9),
              font_size = spec_font_size(x))
  }) %>%
  mutate(Species = cell_spec(
    Species, "latex", color = "white", bold = T,
    background = spec_color(1:10, end = 0.9, option = "A", direction = -1)
  )) %>%
  kable("latex", escape = F, booktabs = T, linesep = "", align = "c")
```

| Sepal.Length | Sepal.Width | Petal.Length | Petal.Width | Species |
|--------------|-------------|--------------|-------------|---------|
| 5.1          | 3.5         | 1.4          | 0.2         | setosa  |
| 4.9          | 3           | 1.4          | 0.2         | setosa  |
| 4.7          | 3.2         | 1.3          | 0.2         | setosa  |
| 4.6          | 3.1         | 1.5          | 0.2         | setosa  |
| 5            | 3.6         | 1.4          | 0.2         | setosa  |
| 5.4          | 3.9         | 1.7          | 0.4         | setosa  |
| 4.6          | 3.4         | 1.4          | 0.3         | setosa  |
| 5            | 3.4         | 1.5          | 0.2         | setosa  |
| 4.4          | 2.9         | 1.4          | 0.2         | setosa  |
| 4.9          | 3.1         | 1.5          | 0.1         | setosa  |

In the example above, I'm using the `mutate` functions from `dplyr`. You don't have to use it. Base R solutions like `iris$Species <- cell_spec(iris$Species, color = "red")` also works.

## Text Specification

If you check the results of `cell_spec`, you will find that this function does nothing more than wrapping the text with appropriate HTML/LaTeX formatting syntax. The result of this function is just a vector of character strings. As a result, when you are writing a `rmarkdown` document or write some text in shiny apps, if you need extra markups other than **bold** or *italic*, you may use this function to **color**, **change font**

**size** or *rotate* your text.

An aliased function `text_spec` is also provided for a more literal writing experience. The only difference is that in LaTeX, unless you specify `latex_background_in_cell = FALSE` (default is `TRUE`) in `cell_spec`, it will define cell background color as `\cellcolor{}`, which doesn't work outside of a table, while for `text_spec`, the default value for `latex_background_in_cell` is `FALSE`.

```
sometext <- strsplit(paste0(
  "You can even try to make some crazy things like this paragraph. ",
  "It may seem like a useless feature right now but it's so cool ",
  "and nobody can resist. ;)"), " ")[[1]]
text_formatted <- paste(
  text_spec(sometext, "latex", color = spec_color(1:length(sometext), end = 0.9),
    font_size = spec_font_size(1:length(sometext), begin = 5, end = 20)),
  collapse = " ")
```

*# To display the text, type `r text\_formatted` outside of the chunk*

You can even try to make some crazy things like this paragraph. It may seem like a useless feature right now but it's so cool and nobody can resist. ;)

## Grouped Columns / Rows

### Add header rows to group columns

Tables with multi-row headers can be very useful to demonstrate grouped data. To do that, you can pipe your kable object into `add_header_above()`. The header variable is supposed to be a named character with the names as new column names and values as column span. For your convenience, if column span equals to

1, you can ignore the =1 part so the function below can be written as ‘add\_header\_above(c(" ", "Group 1" = 2, "Group 2" = 2, "Group 3" = 2)).

```
kable(dt, "latex", booktabs = T) %>%
  kable_styling() %>%
  add_header_above(c(" " = 1, "Group 1" = 2, "Group 2" = 2, "Group 3" = 2))
```

|                   | Group 1 |     | Group 2 |     | Group 3 |       |
|-------------------|---------|-----|---------|-----|---------|-------|
|                   | mpg     | cyl | disp    | hp  | drat    | wt    |
| Mazda RX4         | 21.0    | 6   | 160     | 110 | 3.90    | 2.620 |
| Mazda RX4 Wag     | 21.0    | 6   | 160     | 110 | 3.90    | 2.875 |
| Datsun 710        | 22.8    | 4   | 108     | 93  | 3.85    | 2.320 |
| Hornet 4 Drive    | 21.4    | 6   | 258     | 110 | 3.08    | 3.215 |
| Hornet Sportabout | 18.7    | 8   | 360     | 175 | 3.15    | 3.440 |

In fact, if you want to add another row of header on top, please feel free to do so. Also, since kableExtra 0.3.0, you can specify bold & italic as you do in row\_spec().

```
kable(dt, "latex", booktabs = T) %>%
  kable_styling(latex_options = "striped") %>%
  add_header_above(c(" ", "Group 1" = 2, "Group 2" = 2, "Group 3" = 2)) %>%
  add_header_above(c(" ", "Group 4" = 4, "Group 5" = 2)) %>%
  add_header_above(c(" ", "Group 6" = 6), bold = T, italic = T)
```

|                   | <i><b>Group 6</b></i> |     |         |     |         |       |
|-------------------|-----------------------|-----|---------|-----|---------|-------|
|                   | Group 4               |     |         |     | Group 5 |       |
|                   | Group 1               |     | Group 2 |     | Group 3 |       |
|                   | mpg                   | cyl | disp    | hp  | drat    | wt    |
| Mazda RX4         | 21.0                  | 6   | 160     | 110 | 3.90    | 2.620 |
| Mazda RX4 Wag     | 21.0                  | 6   | 160     | 110 | 3.90    | 2.875 |
| Datsun 710        | 22.8                  | 4   | 108     | 93  | 3.85    | 2.320 |
| Hornet 4 Drive    | 21.4                  | 6   | 258     | 110 | 3.08    | 3.215 |
| Hornet Sportabout | 18.7                  | 8   | 360     | 175 | 3.15    | 3.440 |

## Group rows via labeling

Sometimes we want a few rows of the table being grouped together. They might be items under the same topic (e.g., animals in one species) or just different data groups for a categorical variable (e.g., age < 40, age > 40). With the new function group\_rows() in kableExtra, this kind of task can be completed in one line. Please see the example below. Note that when you count for the start/end rows of the group, you don’t need to count for the header rows nor other group label rows. You only need to think about the row numbers in the “original R dataframe”.

```
kable(mtcars[1:10, 1:6], "latex", caption = "Group Rows", booktabs = T) %>%
  kable_styling() %>%
  group_rows("Group 1", 4, 7) %>%
  group_rows("Group 2", 8, 10)
```

In case some users need it, you can define your own gapping spaces between the group labeling row and previous rows. The default value is 0.5em.

Table 3: Group Rows

|                   | mpg  | cyl | disp  | hp  | drat | wt    |
|-------------------|------|-----|-------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160.0 | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160.0 | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108.0 | 93  | 3.85 | 2.320 |
| <b>Group 1</b>    |      |     |       |     |      |       |
| Hornet 4 Drive    | 21.4 | 6   | 258.0 | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360.0 | 175 | 3.15 | 3.440 |
| Valiant           | 18.1 | 6   | 225.0 | 105 | 2.76 | 3.460 |
| Duster 360        | 14.3 | 8   | 360.0 | 245 | 3.21 | 3.570 |
| <b>Group 2</b>    |      |     |       |     |      |       |
| Merc 240D         | 24.4 | 4   | 146.7 | 62  | 3.69 | 3.190 |
| Merc 230          | 22.8 | 4   | 140.8 | 95  | 3.92 | 3.150 |
| Merc 280          | 19.2 | 6   | 167.6 | 123 | 3.92 | 3.440 |

```
kable(dt, "latex", booktabs = T) %>%
  group_rows("Group 1", 4, 5, latex_gap_space = "2em")
```

|               | mpg  | cyl | disp | hp  | drat | wt    |
|---------------|------|-----|------|-----|------|-------|
| Mazda RX4     | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710    | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |

**Group 1**

|                   |      |   |     |     |      |       |
|-------------------|------|---|-----|-----|------|-------|
| Hornet 4 Drive    | 21.4 | 6 | 258 | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8 | 360 | 175 | 3.15 | 3.440 |

If you prefer to build multiple groups in one step, you can use the short-hand `index` option. Basically, you can use it in the same way as you use `add_header_above`. However, since `group_row` only support one layer of grouping, you can't add multiple layers of grouping header as you can do in `add_header_above`.

```
kable(mtcars[1:10, 1:6], "latex", caption = "Group Rows", booktabs = T) %>%
  kable_styling() %>%
  group_rows(index=c(" " = 3, "Group 1" = 4, "Group 2" = 3))
# Not evaluated. The code above should have the same result as the first example in this section.
```

Note that `kable` has a relatively special feature to handle `align` and it may bring troubles to you if you are not using it correctly. In the documentation of the `align` argument of `kable`, it says:

If `length(align) == 1L`, the string will be expanded to a vector of individual letters, e.g. `'c1c'` becomes `c('c', '1', 'c')`, **unless the output format is LaTeX**.

For example,

```
kable(mtcars[1:2, 1:2], "latex", align = c("c1"))
# \begin{tabular}{l|cl|cl} # Note the column alignment here
# \hline
#   & mpg & cyl \\
# ...
```

LaTeX, somehow shows surprisingly high tolerance on that, which is quite unusual. As a result, it won't throw an error if you are just using `kable` to make some simple tables. However, when you use `kableExtra`

to make some advanced modification, it will start to throw some bugs. As a result, please try to form a habit of using a vector in the `align` argument for `kable` (tip: you can use `rep` function to replicate elements. For example, `c("c", rep("1", 10))`).

## Row indentation

Unlike `group_rows()`, which will insert a labeling row, sometimes we want to list a few sub groups under a total one. In that case, `add_indent()` is probably more appropriate.

For advanced users, you can even define your own css for the group labeling.

```
kable(dt, "latex", booktabs = T) %>%
  add_indent(c(1, 3, 5))
```

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

## Group rows via multi-row cell

Function `group_rows` is great for showing simple structural information on rows but sometimes people may need to show structural information with multiple layers. When it happens, you may consider using `collapse_rows` instead, which will put repeating cells in columns into multi-row cells.

In LaTeX, `collapse_rows` adds some extra hlines to help differentiate groups. You can customize this behavior using the `latex_hline` argument. You can choose from `full` (default), `major` and `none`. Vertical alignment of cells is controlled by the `valign` option. You can choose from “top”, “middle”(default) and “bottom”. Be cautious that the vertical alignment option was only introduced in `multirow` in 2016. If you are using a legacy LaTeX distribution, you will run into trouble if you set `valign` to be either “top” or “bottom”.

```
collapse_rows_dt <- data.frame(C1 = c(rep("a", 10), rep("b", 5)),
                               C2 = c(rep("c", 7), rep("d", 3), rep("c", 2), rep("d", 3)),
                               C3 = 1:15,
                               C4 = sample(c(0,1), 15, replace = TRUE))
kable(collapse_rows_dt, "latex", booktabs = T, align = "c") %>%
  column_spec(1, bold=T) %>%
  collapse_rows(columns = 1:2, latex_hline = "major", valign = "middle")
```

| C1       | C2 | C3 | C4 |
|----------|----|----|----|
| <b>a</b> | c  | 1  | 1  |
|          |    | 2  | 0  |
|          |    | 3  | 1  |
|          |    | 4  | 1  |
|          |    | 5  | 1  |
|          |    | 6  | 1  |
|          |    | 7  | 1  |
|          | d  | 8  | 0  |
|          |    | 9  | 0  |
|          |    | 10 | 0  |
| <b>b</b> | c  | 11 | 1  |
|          |    | 12 | 1  |
|          |    | 13 | 1  |
|          | d  | 14 | 0  |
|          |    | 15 | 1  |

Right now, you can't automatically make striped rows based on collapsed rows but you can do it manually via the `extra_latex_after` option in `row_spec`. This feature is not officially supported. I'm only document it here if you want to give it a try.

```
kable(collapse_rows_dt[-1], "latex", align = "c", booktabs = T) %>%
  column_spec(1, bold = T, width = "5em") %>%
  row_spec(c(1:7, 11:12) - 1, extra_latex_after = "\\rowcolor{gray!6}") %>%
  collapse_rows(1, latex_hline = "none")
```

| C2       | C3 | C4 |
|----------|----|----|
| <b>c</b> | 1  | 1  |
|          | 2  | 0  |
|          | 3  | 1  |
|          | 4  | 1  |
|          | 5  | 1  |
|          | 6  | 1  |
|          | 7  | 1  |
| <b>d</b> | 8  | 0  |
|          | 9  | 0  |
|          | 10 | 0  |
| <b>c</b> | 11 | 1  |
|          | 12 | 1  |
| <b>d</b> | 13 | 1  |
|          | 14 | 0  |
|          | 15 | 1  |

When there are too many layers, sometimes the table can become too wide. You can choose to stack the first few layers by setting `row_group_label_position` to `stack`.

```
collapse_rows_dt <- expand_grid(
  Country = sprintf('Country with a long name %s', c('A', 'B')),
  State = sprintf('State %s', c('a', 'b')),
  City = sprintf('City %s', c('1', '2')),
  District = sprintf('District %s', c('1', '2'))
) %>% arrange(Country, State, City) %>%
  mutate_all(as.character) %>%
  mutate(C1 = rnorm(n()),
```



```

C2 = rnorm(n()))

kable(collapse_rows_dt, "latex",
      booktabs = T, align = "c", linesep = '') %>%
  collapse_rows(1:3, row_group_label_position = 'stack')

```

|                            | City   | District   | C1         | C2         |
|----------------------------|--------|------------|------------|------------|
| Country with a long name A |        |            |            |            |
| State a                    |        |            |            |            |
|                            | City 1 | District 1 | 1.2310087  | 2.2313530  |
|                            |        | District 2 | 0.9826374  | -2.1396163 |
|                            | City 2 | District 1 | 0.0264648  | -0.0388721 |
|                            |        | District 2 | 0.1648380  | -0.7412360 |
| State b                    |        |            |            |            |
|                            | City 1 | District 1 | -1.7238617 | 0.4633016  |
|                            |        | District 2 | 0.0304331  | -0.9037582 |
|                            | City 2 | District 1 | -0.5305438 | 0.5124428  |
|                            |        | District 2 | 1.2224043  | 0.1891501  |
| Country with a long name B |        |            |            |            |
| State a                    |        |            |            |            |
|                            | City 1 | District 1 | 0.7511162  | 0.6856506  |
|                            |        | District 2 | 0.8800045  | -0.7349027 |
|                            | City 2 | District 1 | 1.1543094  | -1.3191297 |
|                            |        | District 2 | -0.2706420 | -0.1317580 |
| State b                    |        |            |            |            |
|                            | City 1 | District 1 | 0.5675130  | 0.1892414  |
|                            |        | District 2 | -1.9030169 | 0.1436275  |
|                            | City 2 | District 1 | -2.2156849 | 0.6222846  |
|                            |        | District 2 | -0.2375696 | -0.2327310 |

To better distinguish different layers, you can format the each layer using `row_group_label_fonts`. You can also customize the hlines to better differentiate groups.

```

row_group_label_fonts <- list(
  list(bold = T, italic = T),
  list(bold = F, italic = F)
)
kable(collapse_rows_dt, "latex",
      booktabs = T, align = "c", linesep = '') %>%
  column_spec(1, bold=T) %>%
  collapse_rows(1:3, latex_hline = 'custom', custom_latex_hline = 1:3,
    row_group_label_position = 'stack',
    row_group_label_fonts = row_group_label_fonts)

```

|                                   | City   | District   | C1         | C2         |
|-----------------------------------|--------|------------|------------|------------|
| <i>Country with a long name A</i> |        |            |            |            |
| State a                           | City 1 | District 1 | 1.2310087  | 2.2313530  |
|                                   |        | District 2 | 0.9826374  | -2.1396163 |
|                                   | City 2 | District 1 | 0.0264648  | -0.0388721 |
|                                   |        | District 2 | 0.1648380  | -0.7412360 |
| State b                           | City 1 | District 1 | -1.7238617 | 0.4633016  |
|                                   |        | District 2 | 0.0304331  | -0.9037582 |
|                                   | City 2 | District 1 | -0.5305438 | 0.5124428  |
|                                   |        | District 2 | 1.2224043  | 0.1891501  |
| <i>Country with a long name B</i> |        |            |            |            |
| State a                           | City 1 | District 1 | 0.7511162  | 0.6856506  |
|                                   |        | District 2 | 0.8800045  | -0.7349027 |
|                                   | City 2 | District 1 | 1.1543094  | -1.3191297 |
|                                   |        | District 2 | -0.2706420 | -0.1317580 |
| State b                           | City 1 | District 1 | 0.5675130  | 0.1892414  |
|                                   |        | District 2 | -1.9030169 | 0.1436275  |
|                                   | City 2 | District 1 | -2.2156849 | 0.6222846  |
|                                   |        | District 2 | -0.2375696 | -0.2327310 |

## Table Footnote

Now it's recommended to use the new `footnote` function instead of `add_footnote` to make table footnotes.

Documentations for `add_footnote` can be found [here](#).

There are four notation systems in `footnote`, namely `general`, `number`, `alphabet` and `symbol`. The last three types of footnotes will be labeled with corresponding marks while `general` won't be labeled. You can pick any one of these systems or choose to display them all for fulfilling the APA table footnotes requirements.

```
kable(dt, "latex", align = "c") %>%
  kable_styling(full_width = F) %>%
  footnote(general = "Here is a general comments of the table. ",
    number = c("Footnote 1; ", "Footnote 2; "),
    alphabet = c("Footnote A; ", "Footnote B; "),
    symbol = c("Footnote Symbol 1; ", "Footnote Symbol 2")
  )
```

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

*Note:*

Here is a general comments of the table.

<sup>1</sup> Footnote 1;

<sup>2</sup> Footnote 2;

<sup>a</sup> Footnote A;

<sup>b</sup> Footnote B;

\* Footnote Symbol 1;

<sup>†</sup> Footnote Symbol 2

You can also specify title for each category by using the `***_title` arguments. Default value for `general_title` is “Note:” and “” for the rest three. You can also change the order using `footnote_order`. You can even display footnote as chunk texts (default is as a list) using `footnote_as_chunk`. The font format of the titles are controlled by `title_format` with options including “*italic*” (default), “**bold**” and “underline”.

```
kable(dt, "latex", align = "c", booktabs = T) %>%
  footnote(general = "Here is a general comments of the table. ",
    number = c("Footnote 1; ", "Footnote 2; "),
    alphabet = c("Footnote A; ", "Footnote B; "),
    symbol = c("Footnote Symbol 1; ", "Footnote Symbol 2"),
    general_title = "General: ", number_title = "Type I: ",
    alphabet_title = "Type II: ", symbol_title = "Type III: ",
    footnote_as_chunk = T, title_format = c("italic", "underline")
  )
```

|                   | mpg  | cyl | disp | hp  | drat | wt    |
|-------------------|------|-----|------|-----|------|-------|
| Mazda RX4         | 21.0 | 6   | 160  | 110 | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0 | 6   | 160  | 110 | 3.90 | 2.875 |
| Datsun 710        | 22.8 | 4   | 108  | 93  | 3.85 | 2.320 |
| Hornet 4 Drive    | 21.4 | 6   | 258  | 110 | 3.08 | 3.215 |
| Hornet Sportabout | 18.7 | 8   | 360  | 175 | 3.15 | 3.440 |

*General:* Here is a general comments of the table.

*Type I:* <sup>1</sup> Footnote 1; <sup>2</sup> Footnote 2;

*Type II:* <sup>a</sup> Footnote A; <sup>b</sup> Footnote B;

*Type III:* \* Footnote Symbol 1; <sup>†</sup> Footnote Symbol 2

If you need to add footnote marks in a table, you need to do it manually (no fancy) using `footnote_marker_***()`. Remember that similar with `cell_spec`, you need to tell this function whether you want it to do it in HTML (default) or LaTeX. You can set it for all using the `knitr.table.format` global option. Also, if you have ever used `footnote_marker_***()`, you need to put `escape = F` in your `kable` function to avoid escaping of special characters. Note that if you want to use these `footnote_marker` functions in `kableExtra` functions like `group_rows` (for the row label) or `add_header_above`, you need to set `double_escape = T` and `escape = F` in those functions. I’m trying to find other ways around. Please let me know if you have a good idea and are willing to contribute.

```
dt_footnote <- dt
names(dt_footnote)[2] <- paste0(names(dt_footnote)[2],
  # That "latex" can be eliminated if defined in global
  footnote_marker_symbol(1, "latex"))
```



```
dt_lb <- data.frame(
  Item = c("Hello\nWorld", "This\nis a cat"),
  Value = c(10, 100)
)

dt_lb %>%
  mutate_all(linebreak) %>%
  kable("latex", booktabs = T, escape = F,
        col.names = linebreak(c("Item\n(Name)", "Value\n(Number)"), align = "c"))
```

| Item<br>(Name)   | Value<br>(Number) |
|------------------|-------------------|
| Hello<br>World   | 10                |
| This<br>is a cat | 100               |

At the same time, since **kableExtra** 0.8.0, all **kableExtra** functions that have some contents input (such as **footnote** or **group\_rows**) will automatically convert `\n` to linebreaks for you in both LaTeX and HTML.

## Table on a Landscape Page

Sometimes when we have a wide table, we want it to sit on a designated landscape page. The new function **landscape()** can help you on that. Unlike other functions, this little function only serves LaTeX and doesn't have a HTML side.

```
kable(dt, "latex", caption = "Demo Table (Landscape)[note]", booktabs = T) %>%
  kable_styling(latex_options = c("hold_position")) %>%
  add_header_above(c(" ", "Group 1[note]" = 3, "Group 2[note]" = 3)) %>%
  add_footnote(c("This table is from mtcars",
                 "Group 1 contains mpg, cyl and disp",
                 "Group 2 contains hp, drat and wt"),
               notation = "symbol") %>%
  group_rows("Group 1", 4, 5) %>%
  landscape()
```

Table 5: Demo Table (Landscape)\*

|                   | Group 1 <sup>†</sup> |     |      | Group 2 <sup>‡</sup> |      |       |
|-------------------|----------------------|-----|------|----------------------|------|-------|
|                   | mpg                  | cyl | disp | hp                   | drat | wt    |
| Mazda RX4         | 21.0                 | 6   | 160  | 110                  | 3.90 | 2.620 |
| Mazda RX4 Wag     | 21.0                 | 6   | 160  | 110                  | 3.90 | 2.875 |
| Datsun 710        | 22.8                 | 4   | 108  | 93                   | 3.85 | 2.320 |
| <b>Group 1</b>    |                      |     |      |                      |      |       |
| Hornet 4 Drive    | 21.4                 | 6   | 258  | 110                  | 3.08 | 3.215 |
| Hornet Sportabout | 18.7                 | 8   | 360  | 175                  | 3.15 | 3.440 |

\* This table is from mtcars

<sup>†</sup> Group 1 contains mpg, cyl and disp

<sup>‡</sup> Group 2 contains hp, drat and wt

## Use LaTeX table in HTML or Word

If you want to include a LaTeX rendered table in your HTML or Word document, or if you just want to save table as an image, you may consider using `kable_as_image()`. Note that this feature requires you to have `magick` installed (`install.packages("magick")`). Also, if you are planning to use it on Windows, you need to install Ghostscript. This feature may not work if you are using `tinytex`. If you are using `tinytex`, please consider using other alternatives to this function.

```
# Not evaluated.

# The code below will automatically include the image in the rmarkdown document
kable(dt, "latex", booktabs = T) %>%
  column_spec(1, bold = T) %>%
  kable_as_image()

# If you want to save the image locally, just provide a name
kable(dt, "latex", booktabs = T) %>%
  column_spec(1, bold = T) %>%
  kable_as_image("my_latex_table")
```

## From other packages

Since the structure of `kable` is relatively simple, it shouldn't be too difficult to convert HTML or LaTeX tables generated by other packages to a `kable` object and then use `kableExtra` to modify the outputs. If you are a package author, feel free to reach out to me and we can collaborate.

### **tables**

The latest version of `tables` comes with a `toKable()` function, which is compatible with functions in `kableExtra` ( $\geq 0.9.0$ ).